

PUMPING SYSTEM

ANIVARYA™
P U M P S



- ◆ 15 Years Experience
- ◆ Compact Design
- ◆ Easy Installation & Operation
- ◆ Easy Selection
- ◆ Easy Maintenance

Capacity : up to 2000 lpm.

Size : ½" to 12"

Pressure : up to 40 bar

Temperature : 120° c

PUMPING SYSTEM

APPLICATION



Gear Box &
Machine Tools



Steel Plant

Oil Fired Furnace

Sugar Machineries



Cement &
Coal Mill

Compressors

Power Plants

Diesel Generators



Oil Filtration/
Recirculating to
Ensure Cleaning



Fluid Handling Systems :

- Fuel Loading & Unloading System
- Force Feed Lubrication System
- Fuel Oil Pumping & Heating System
- Oil Filtration System
- Oil Circulation System

Standard Equipment

Pumps: Positive Displacement Gear/Screw Pump
 Coupling: Flexible Jaw Coupling
 Motor: TEFC, Foot Mounted, 3ph Energy Efficient Electric Motors.
 Valves: Ball Valve, Gate Valve, Check Valve, Y-Strainer
 Filters: Single Basket Filter, Duplex Basket Filter.
 Pressure Gauge : Glycerin Filled Pressure Gauge.

Optional Equipments

Flow Meter
 Temperature Meter
 Overload Protection Switch
 Heat Exchanger/Coolers

Note: Due to Design Improvements, Specification & Performance are Subject to Change Without Prior Notice



2716, Phase IV, G.I.D.C. Estate, Wadhwanacity-363 035. Gujarat-India
 Tel.: +91-2752-241479, Fax: +91-2752-242479
 Email: mail@anivaryapumps.com
 Website: www.anivaryapumps.com